



## PLUS 56-08 VS

Stationär ljuddämpad skruvkompressor, med varvtalstyrd drift

- + Kompakt design, lätt placerad och enkel installation
- + Poly V-remdrivet skruvblock, effektivt och driftsäkert
- + Kompletta enhet med kyltork och luftbehållare, lätt placerad och enkel installation
- + Kontrollbox EasyTronic IV som övervakar driften
- + Termostatstyrd centrifugal fläkt, effektiv och tyst kylning
- + Förfilter-panel, ren och dammfri insida för ökad brukstid
- + Spin-On filter för enkel och effektivt underhåll

Art.nr.	Benämning	Volt	kW	l/min	Bar	dBa	Vikt kg	Dim lxbxh cm
100 103 061	PLUS 56-08 VS	400/3	55	9.300/3.700	8	70	1686	180 x 110 x 215

MARS 2019

## TECHNICAL FEATURES

Technical characteristics	Type	56
Working pressure	bar g	7,5
Air-end	type	FS250
Max F.a.d (according to ISO 1217 )	l/min	9300
Min F.a.d. (according to ISO 1217 )	l/min	3500
Oil quantity	l	36
Oil quantity for topping-up	l	7
Max air temperature above ambient	°C	11
Re-claimable heat	kJ/h	188000
Cooling fan rate	m3/h	7800
Oil carry over	mg/m3	2-4
Electric motor	type	250 B3
Rated power	kW	55
Max. power absorbed, ventilation included	kW	60
Electrical box protection class	IP	54
Maximum ambient temperature	°C	+2/+45
Noise level (according Pneurop/Cagi PN2CPTC2)	dB(A)	70
Electrical data		
Voltage	V/Ph/Hz	400/3 ~/50
Auxiliary voltage	V/Ph/Hz	24/1~/50
Start-up absorbed current	A	
Max. absorbed current, ventilation included	A	97
Idle running absorbed power	kW	15,5
Electrical motor protection class	IP	55
Motor insulation class		F
Service factor		1,1
Protection devices		
Max oil temperature	°C	110
Pre-alarm oil temperature	°C	105
Motor overload switch setting	A	PTC
Safety valve setting	bar	14
Dimensions		
Length	mm	1800
Width	mm	1090
Height	mm	1860
Weight	kg	1686
Air outlet size	G	2"

