




100% PVC



-25°C - +60°C



10 - 100 m

## Ultra Softech braided PVC hose

### Features

Very soft and flexibility UV and water resistant high quality PVC raw material.  
Hose also meets RoHS requirement and Silicon-free.

### Customer benefits

Best ergonomics and handling with tools  
Long lifetime and flexibility for cold areas  
Outstanding tensibility & tear strength  
Best airflow and perfect function for all connections, including direct fit to tools or couplings/plugs

A very Rubber look-a-like hose.  
Optional high-flow fittings with / without ball bearing, with plastic spring guard and all with BSPP direct seal system.

### Technical data

Tubing material: PVC (100%)  
Standard color: Medium blue  
Working pressure: 20 bar (at 23°C)  
Burst pressure: 60 bar (at 23°C)  
Temperature range: -25°C ~ + 60°C

SofTech PVC BRAIDED HOSES & SETS  
Versions and technical data

Hose ID (mm)	Hose OD (mm)	Total Length per Roll* (m)	Part Number
8	12.5	100	126.3000
8	12.5	50	126.3500
10	15.0	100	126.8000
10	15.0	50	126.8500

(Sold in other lengths on request)

FITTINGS w/pressed on	Hose ID x OD (mm)	Work Length (m)	Connection*	Part Number
Female thread	10 x 15 mm	10	3/8" M thread	176.5100
		15	3/8" M thread	176.5200
		20	3/8" M thread	176.5300
Quick coupling /Plug	10 x 15 mm	10	Eur-std coupler	176.5105
		15	Eur-std coupler	176.5205
		20	Eur-std coupler	176.5305