



Alternative of connection:



- pressed on female thread



- pressed on coupling / plug

RubTech - a flexible braided Rubber hose

Features

Long lifetime and great flexibility for compressed air and water resistant

Top quality SBR raw material 80 Shore A

Superior abrasion resistance and unkinkable

Optional
with pressed on fittings or quick couplings

Customer benefits

Best ergonomics and handling with tools

Long lifetime and flexibility for cold areas

Outstanding tensibility & tear strength

Best airflow and perfect function for all connections, including direct fit to tools or couplings/plugs

Technical data

Tubing material: SBR (100% PUR)

Standard color: Black/Grey

Working pressure: 16 bar (at 23°C)

Burst pressure: 60 bar (at 23°C)

Temperature range: -30°C ~ + 70°C


RUBBER RubTech BRAIDED HOSE Versions and technical data

Hose ID (mm)	Hose OD (mm)	Total Length per Roll (m)	Part Number
8	15	50	131.2500
10	17	100	131.3000
		50	131.3500
13	20	100	131.4000
		50	131.4500

(Other precut lengths on request)


RUBBER RubTech BRAIDED HOSE SETS Versions and technical data

🇸🇪 ASSEMBLED IN SWEDEN

	Hose ID x OD (mm)	Work Length (m)		Connection BSP	Part Number
pressed on FITTINGS	10 x 17	10		3/8" M tread	172.5101
		15		3/8" M tread	172.5201
		20		3/8" M tread	172.5301
pressed on FITTINGS	13 x 20	10		1/2" M tread	172.7101
		15		1/2" M tread	172.7201
		20		1/2" M tread	172.7301

RUBBER RubTech BRAIDED HOSE SETS WITH COUPLING/PLUG Versions and technical data

🇸🇪 ASSEMBLED IN SWEDEN

	Hose ID x OD (mm)	Work Length (m)		Connection	Part Number
pressed on COUPLINGS	10 x 17	10		Eur-std coupler	172.5125
		15		Eur-std coupler	172.5225
		20		Eur-std coupler	172.5305
pressed on COUPLINGS	13 x 20	10		Eur-std coupler	172.7125
		15		Eur-std coupler	172.7225
		20		Eur-std coupler	172.7305

(*Other Coupling/Plug on request)