



| Dimension (mm): | | | | |
|-----------------|-----|-----|-----|----|
| | A | B | C | D |
| 317 : | 190 | 400 | 277 | 85 |

Compound workplace reel

Features & Benefits

Casing made in shock proof PP/Polypropylene
- suitable for tough environments

Unoflex high quality braided hose, soft & comfortable handling
even at very low temperatures.

Blue PU Ehter in \varnothing : 8x12mm

Hose lenght: up to 16 meter

- Store the hose completely back to the reel

Full-flow axle design

Revolving hinge with 200° rotation

- Easy to reach your application accurately

Model 317 has a hose guide and safety retraction mechanism.

Plastic spring proction and BSPP thread with o-ring sealing

Optional Accessories

High-flow Coupling / Plug

Safety Coupling

1/4" or 3/8" ball-bearing swivel fittings

Special versions on request

Other colors or qualities of hoses

Other length

Other colors of casing



COMPOUND REEL SERIES - Versions and technical data

| Version | Hose Length | Hose \varnothing mm | Lead Hose | Hose Material | Temperature & Pressure | Thread In/Out | Weight | Part Number |
|--------------|-------------|-----------------------|-----------|------------------|-------------------------------------|------------------|--------|-------------|
| 317 PU Polar | 16 m | 8 x 12 | 1.5 m | Ehter-PUR (100%) | - 30°C to +60°C 12 bar (174 psi) | 1/4" - 1/4" BSPP | 5,0 kg | 317.1200 |