



Interchangeability: Rectus 25/26, Cejn 320


Max. Pressure: 35 Bar

Material:	Standard	Stainless Steel AISI 316
Coupling:	Brass Nickel Plated	AISI 316
Sleeve:	Steel Nickel Plated	AISI 316
Valve:	Brass	AISI 316
Plug:	Steel Nickel Plated	AISI 316
Seals:	NBR	Viton

Temp. range: -20 °C - +100 °C
Flow: 1850 l/min




Coupling
Hose Barb




Art. No.	Dim
251006	6mm
251008	8mm
251009	9mm
251010	10mm
251013	13mm

Coupling
Tapered Male Threads



Art. No.	Dim
251113	1/4"
251117	3/8"
251121	1/2"

Coupling
Female Threads




Art. No.	Dim
251213	1/4"
251217	3/8"
251221	1/2"

Plug
Hose Barb




Art. No.	Dim
255006	6mm
255008	8mm
255009	9mm
255010	10mm
255013	13mm

Plug
Tapered Male Threads




Art. No.	Dim
255110	1/8"
255113	1/4"
255117	3/8"
255121	1/2"

Plug
Female Threads




Art. No.	Dim
255210	1/8"
255213	1/4"
255217	3/8"
255221	1/2"

Y-coupling
3 outlets w/series 25




Art. No.	Dim
25Y317	3/8"
25Y321	1/2"

Y-coupling
2 outlets w/series 25



Art. No.	Dim
25Y217	3/8"
25Y221	1/2"


Y-Coupling
2 outlets w/series 25 / plug



Art. No.	Dim
25Y21725	3/8"


Stainless Steel AISI 316

Coupling
Hose Barb




251006EV	6mm
251008EV	8mm
251009EV	9mm
251010EV	10mm
251013EV	13mm

Coupling
Tapered Male Threads



251113EV	1/4"
251117EV	3/8"
251121EV	1/2"

Coupling
Female Threads




251213EV	1/4"
251217EV	3/8"
251221EV	1/2"

Plug
Hose Barb




255006E	6mm
255008E	8mm
255009E	9mm
255010E	10mm
255013E	13mm

Plug
Tapered Male Threads



255113E	1/4"
255117E	3/8"
255121E	1/2"

Plug
Female Threads



255213E	1/4"
255217E	3/8"
255221E	1/2"




Interchangeability: Rectus 25/26, Cejn 320
Material: Standard
Coupling: Brass Nickel Plated
Sleeve: Steel Nickel Plated
Valve: Brass
Plug: Steel Nickel Plated
Seals: NBR

Max. Pressure: 35 Bar
Temp. range: -20 °C - +100 °C
Flow: 1850 l/min




Coupling
Hose Barb




Art. No.	Dim
251006B	6mm
251008B	8mm
251009B	9mm
251010B	10mm
251013B	13mm

Coupling
Tapered Male Threads




Art. No.	Dim
251113B	1/4"
251117B	3/8"
251121B	1/2"

Coupling
Female Threads




Art. No.	Dim
251213B	1/4"
251217B	3/8"
251221B	1/2"

Plug
Hose Barb




Art. No.	Dim
255006B	6mm
255008B	8mm
255009B	9mm
255010B	10mm
255013B	13mm

Plug
Tapered Male Threads




Art. No.	Dim
255113B	1/4"
255117B	3/8"
255121B	1/2"

Plug
Female Threads




Art. No.	Dim
255213B	1/4"
255217B	3/8"
255221B	1/2"




Y-coupling
3 outlets w/series 25

Art. No.	Dim
25Y317B	3/8"
25Y321B	1/2"



Y-coupling
2 outlets w/series 25

Art. No.	Dim
25Y217B	3/8"
25Y221B	1/2"



Y-Coupling
2 outlets
w/series 25 / plug

Art. No.	Dim
25Y21725B	3/8"




SWING SAFETY COUPLING
- SAFETY SWING FOR VENTING AND DISCONNECT

Material:	Standard	Interchangeability:	Rectus 25, 26 Cejn 320
Coupler Body:	Steel Nickel Plated	Max. Pressure:	15 Bar
Back part:	Aluminium	Temp. range:	-20 °C - +100 °C
Seals:	NBR	Flow:	1750 l/min




Coupling
Hose Barb

Art. No.	Dim
25S1006-SC	6mm
25S1008-SC	8mm
25S1010-SC	10mm
25S1013-SC	13mm



Coupling
Male Threads

Art. No.	Dim
25S1113-SC	1/4"
25S1117-SC	3/8"
25S1121-SC	1/2"




Coupling
Female Threads

Art. No.	Dim
25S1213-SC	1/4"
25S1217-SC	3/8"
25S1221-SC	1/2"



PUSH BUTTON SAFETY COUPLING
SAFETY - 2 PUSH FOR DISCONNECT

Material:	Standard	Interchangeability:	Rectus 25, 26 Cejn 320
Coupler Body:	Steel Chrome Plated	Max. Pressure:	12 Bar
Inner part:	Aluminium - Eloxal	Temp. range:	-15 °C - +70 °C
Back part:	Brass Nickel Plated	Flow:	1750 l/min
Valve:	Steel chrome Plated		
Seals:	NBR		




Coupling
Hose Barb 2 push button

Art. No.	Dim
25S1006-2	6mm
25S1008-2	8mm
25S1010-2	10mm
251013-2	13mm



Coupling
Male Threads 2 push button

Art. No.	Dim
25S1113-2	1/4"
25S1117-2	3/8"
25S1121-2	1/2"



Coupling
Female Threads 2 push button

Art. No.	Dim
25S1213-2	1/4"
25S1217-2	3/8"
25S1221-2	1/2"