

PRO 500/150 PRIME S HD

Cod. 100200405

Heavy duty cycle oil-free compressor, air output at 8 bar 1140 l/min, 500 l tank. The operation of the compressor is regulated by an electronic control unit installed directly on the compressor. The compressor is supplied without air filtration.


Applications:

- Dental clinics
- Dental laboratories and CAD-CAM milling machines
- Laboratories: rheometers, viscometers, chromatography, analyzers
- Ophthalmology
- Sterilization devices
- Air breathing systems
- Cabinets for endoscopy
- Food packaging
- Beverage
- Gas productions



Air capacity		FAD @ 8bar		Motor	Voltage Hz	Receiver	Noise Level	Duty Cycle	max P.
m ³ /min	l/min	m ³ /min	l/min	kW	400V 50/60Hz	l	db(A)	100 %	bar
2.16	2160	1.14	1140	15		500	79		10

Air delivery performance



Maintenance kits

Kit.	Description	Type	Hours
------	-------------	------	-------

<p>TA-FL-0013-K-SCP</p>	<p>TANDEM PRIME 6+6+6 Version S</p> <p>The ordinary maintenance kit TANDEM PRIME 6+6+6 (500/150 S) without dryer.</p> <p>Comprehends:</p> <ul style="list-style-type: none"> • 18 suction filters, code: TA-FL-058-C • 1 filter cartridge, code: TA-FL-001-C-SM • 1 O-ring, code: TA-FL-001-OR • 6 non-return valve pads, cod: CO-PV-001 <p>Change the filter cartridges every year.</p>	<p>Ordinary</p>	<p>1.000h/1y</p>
<p>PR-GC-038-K-SCP</p>	<p>Kit 500/150 TANDEM PRIME - 6 + 6 + 6</p> <p>Extraordinary maintenance kit for oil-free compressors TANDEM PRIME 5+5+5 Kw versions (TANDEM PRIME 6+6+6).</p> <p>Composed of:</p> <ul style="list-style-type: none"> • 18 suction filters, code: TA-FL-058-C • 18 O-rings, code: MA-PC018 • 18 piston rings , code: MA-MG00001 • 18 piston guide rings, code: MA-MG00003 • 18 expansion rings for the segments, code: MA-MG00024 • 18 complete valve plates, code: MA-MG-02002P-C-P • 6 non-return valve pads, cod: CO-PV-001 	<p>Extraordinary</p>	<p>4.000h/4y</p>